

In the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application.

1. (Previously presented) A fitment comprising:
a spout having upper and lower ends;
a frangible membrane sealing off said spout and having a peripheral edge joined to said spout along a line of weakness; and
a gripping member adapted to facilitate removal of said frangible membrane from said spout, said gripping member including a semicircular member having first and second terminal ends, said first end being connected to said frangible membrane adjacent said line of weakness, and said second end being remotely located from said first end and unconnected to said frangible membrane;

wherein said frangible membrane and said gripping member are monolithically formed.

2. (Original) A fitment according to claim 1 wherein said semicircular member has an inner diameter wall and an outer diameter wall, said fitment further comprising gripping protrusions extending radially inward from said inner diameter wall.

3. (Original) A fitment according to claim 1 wherein said semicircular member is helically shaped.

4. (Original) A fitment according to claim 1 wherein said second end of said semicircular member is located above said upper end of said spout.

5. (Original) A fitment according to claim 1 wherein said semicircular member extends approximately 270°.

6-14. (Cancelled)

15. (Currently amended) A fitment comprising:
a spout having an upper end and a lower ~~[[ends]]~~ end;
a frangible membrane sealing off said spout and having a peripheral edge joined to said spout along a line of weakness;
a gripping member adapted to facilitate removal of said frangible membrane from said spout, said gripping member including a horizontally extending member having a lower edge and a first end, said first end being connected to said frangible membrane adjacent said line of weakness; and
a frangible connection interconnecting a portion of said lower edge of said horizontally extending member and an adjacent portion of said upper end of said spout.
16. (Original) A fitment according to claim 15 wherein said gripping member further comprises a second terminal end, said second end being remotely located from said first end.
17. (Original) A fitment according to claim 15 wherein said horizontally extending member extends at least approximately 270° along said upper end of said spout.
18. (Previously presented) A fitment according to claim 15 wherein said horizontally extending member comprises a lower tapered edge which terminates at said frangible connection.
19. (Original) A fitment according to claim 15 wherein a web interconnects said gripping member and said frangible membrane adjacent said line of weakness.
20. (Original) A fitment according to claim 15 further comprising a stop adapted to limit propagation along said frangible connection, said stop interrupts said frangible connection adjacent said first end of said horizontally extending member.

21. (Original) A fitment according to claim 20 wherein said stop comprises an aperture in said frangible connection adjacent said first end of said horizontally extending member.

22. (Original) A fitment according to claim 15 wherein said horizontally extending member of said gripping member includes cap-engaging structure.

23. (Original) A fitment according to claim 22 wherein said cap-engaging structure includes an external thread adapted to cooperate with an internal thread of a cap.